PAT-NO:

JP362246923A

DOCUMENT-

JP 62246923 A

**IDENTIFIER:** 

TITLE:

RESIN COMPOSITION FOR CARBON FIBER

COMPOSITE MATERIAL

**PUBN-DATE:** 

October 28, 1987

## INVENTOR-INFORMATION:

NAME

COUNTRY

WATANABE, KENZO TODA, ATSUSHI

## ASSIGNEE-INFORMATION:

NAME

COUNTRY

MITSUBISHI CHEM IND LTD N/A

APPL-NO:

JP61089397

**APPL-DATE:** April 18, 1986

INT-CL (IPC): C08 G 059/40, C08 G 059/50, C08 J 005/24, C08 L 063/00

## **ABSTRACT:**

PURPOSE: To obtain a resin composition for carbon fiber composite materials, excellent in heat resistance, toughness, etc., by mixing an epoxy resin based on a hydantoin epoxy resin with 4,4'-diaminodiphenyl sulfone and a specified rubber component.

CONSTITUTION: The purpose resin composition for carbon fiber composite materials is prepared by using an epoxy resin (A) containing at least 50wt%

11/2/2006, EAST Version: 2.1.0.14

hydantoin <u>epoxy</u> resin with 4,4'-diaminodiphenyl sulfone (B) and a carboxyl group-terminated liquid <u>butadiene/acrylonitrile rubber</u> and/or a reaction product thereof (C) with an <u>epoxy</u> compound as principal components. Prepregs are formed by impregnating carbon fiber with the obtained resin composition and the prepregs are press-molded to obtain a carbon fiber composite useful as a structural material for aircraft.

COPYRIGHT: (C)1987,JPO&Japio

11/2/2006, EAST Version: 2.1.0.14